

BONUFLEX



INSULATED PVC ADHESIVE HOSE

APPLICATION AREAS:

- WASTE WATER EXTRACTION
- WATER RECIRCULATION
- HYDROMASSAGE BATHTUBS
- DRAINS
- FLEXIBLE EXTERNAL PIPING

HOSE CHARACTERISTICS:

- COLOR GREY / RAL 7046
- EXCELLENT TEMPERATURE RESISTANCE FROM -10°C TO +55°C
- DESIGNED FOR INDOOR AND OUTDOOR APPLICATIONS WITH ADHESIVE FITTINGS
- CHLORINE AND SALT WATER RESISTANT (MAX. 30%)
- DIN EN ISO 3994
- HALOGEN-FREE

MAIN FEATURE:

- THERMAL INSULATION MADE OF CLOSED-CELL PE FOAM (0.038 W/m*K)
- RESISTANT TO AGEING
- WEATHER-RESISTANT
- HDPE OUTER JACKET



Item no.	Inner diameter	Wall thickness	Outer diameter	Roll dimensions	PN	roll length	PU pallet
0310107M	50 mm	3,5 mm	75 mm	125 x 35 cm	5	12 m	96 m
0310104M	50 mm	3,5 mm	75 mm	125 x 35 cm	5	25 m	175 m
0310105M	63 mm	4,0 mm	90 mm	130 x 45 cm	5	25 m	150 m
0310106M	75 mm	4,5 mm	110 mm	140 x 55 cm	3	25 m	125 m

Subject to technical changes and printing errors. All illustrations are symbolic images.
No liability can be derived from this. We accept no liability for damage resulting from improper use.